

Training on Galaxy: Metabarcoding




March 2024 - Webinar

FROGS Practice on ITS data and Workflow creation

LUCAS AUER, MARIA BERNARD, LAURENT CAUQUIL, MAHENDRA MARIADASSOU, GÉRALDINE PASCAL & OLIVIER RUÉ

What is a ITS ?

ITS: Internal Transcribed Spacer



What is a ITS ?

- Size polymorphism of ITS (from 361 to 1475 bases in UNITE 7.1)
- Highly conserved regions of the neighboring of ITS1 and ITS2
- Lack of a generalist and abundant ITS databank (several small specialized databanks)
- Multiple copies* (14 to 1400 copies (mean at 113, median at 80))
- Do not target Glomeromycetes/Glomeromycota (→ alternative: 18S)



If your sequencing platform preprocesses your data, it has to keep short and long sequences

* <https://doi.org/10.1111/mec.14995>

ITS data from manipulated organic soil (MOS network)



While in the past forest biomass exports concerned only trunks, these exports recently increased and now concern also the branches and smaller parts that were previously left on the ground (for pellet production).

The [MOS network](#) (18 sites in France) was designed to reveal the long-term effects of intense biomass exports on soil fertility and biodiversity. Different treatment of biomass export are applied with or without supplementation of nutrients.

The aim is to analyse the **impact** of these new forestry practices on **soil microbiota** and **tree health**.


The present dataset concerned one of the site (Champenoux) after 5 years of total Organic Matter removal (OMR treatment : all the organic matter on the ground including leaves was removed), **with** our **without nitrogen supplementation**.


- 5 replicates Control x 2 treatments, 5 replicates OMR x 2 treatments
- DNA is extracted and **ITS1** is sequenced
- 2 x 250 bp Illumina MiSeq
- Primer 5': CTTGGTCATTTAGAGGAAGTAA
- Primer 3': GCATCGATGAAGAACGCAGC

Metadata for these samples

Samples	kept	Replicas	Incubation	Nitrogen	Forest_management	Quality	Treatment
Ph203	79.76	3	T4	Nitrogen_supplementation	Control	Low degradability	Control_with_N
Ph212	77.64	2	T4	Nitrogen_supplementation	Control	Low degradability	Control_with_N
Ph217	80.26	5	T4	Nitrogen_supplementation	Control	Low degradability	Control_with_N
Ph222	78.65	1	T4	Nitrogen_supplementation	Control	Low degradability	Control_with_N
Ph224	77.18	4	T4	Nitrogen_supplementation	Control	Low degradability	Control_with_N
Ph237	79.68	1	T4	Control	Control	Low degradability	Control
Ph241	78.7	2	T4	Control	Control	Low degradability	Control
Ph243	76.38	4	T4	Control	Control	Low degradability	Control
Ph246	76.37	5	T4	Control	Control	Low degradability	Control
Ph250	77.37	3	T4	Control	Control	Low degradability	Control
Ph407	72.52	3	T4	Nitrogen_supplementation	OMR	Low degradability	OMR_with_N
Ph414	64.98	4	T4	Nitrogen_supplementation	OMR	Low degradability	OMR_with_N
Ph415	78.13	2	T4	Nitrogen_supplementation	OMR	Low degradability	OMR_with_N
Ph417	71.17	1	T4	Nitrogen_supplementation	OMR	Low degradability	OMR_with_N
Ph423	75.2	5	T4	Nitrogen_supplementation	OMR	Low degradability	OMR_with_N
Ph428	73.48	2	T4	Control	OMR	Low degradability	OMR
Ph433	73.21	5	T4	Control	OMR	Low degradability	OMR
Ph434	74.01	3	T4	Control	OMR	Low degradability	OMR
Ph439	74.15	1	T4	Control	OMR	Low degradability	OMR
Ph449	73.77	4	T4	Control	OMR	Low degradability	OMR


Overview






FROGS Pipeline for ITS







Problematic:
some ITS reads (Miseq sequencing) are non-overlapping
sequences




Consequence: during bioinformatics process, these reads are lost and underlying organisms will be never represented in the abundance table.



Solution: in preprocess step – creation of “FROGS combined” sequences





FROGS_0 Demultiplex reads Attribute reads to samples in function of inner barcode
FROGS_1 Pre-process merging, denoising and dereplication
FROGS_2 Clustering swarm Single-linkage clustering on sequences
FROGS_Cluster_Stat Process some metrics on clusters
FROGS_3 Remove chimera Remove PCR chimera in each sample
FROGS_4 Cluster filters Filters clusters on several criteria.
FROGS ITSx Extract the highly variable ITS1 and ITS2 subregions from ITS sequences
FROGS_5 Taxonomic affiliation Taxonomic affiliation of each ASV's seed by RDPtools and BLAST
FROGS_6 Affiliation_Stat Process some metrics on taxonomies

Basic tools

FROGSSTAT Phyloseq Import Data from 3 files: biomfile, samplefile, treefile
FROGSSTAT Phyloseq Composition Visualisation with bar plot and composition plot
FROGSSTAT Phyloseq Alpha Diversity with richness plot
FROGSSTAT Phyloseq Beta Diversity distance matrix
FROGSSTAT Phyloseq Sample Clustering of samples using different linkage methods
FROGSSTAT Phyloseq Structure Visualisation with heatmap plot and ordination plot
FROGSSTAT Phyloseq Multivariate Analysis Of Variance perform Multivariate Analysis of Variance (MANOVA)
FROGSSTAT DESeq2 Preprocess import a Phyloseq object and prepare it for DESeq2 differential abundance analysis a
FROGSSTAT DESeq2 Visualisation extract and visualise differentially abundant ASVs or functions

Statistics tools

FROGS Tree Reconstruction of phylogenetic tree
FROGS Affiliation Filters Filters ASVs on several affiliation criteria
FROGS Affiliation postprocess Aggregates ASVs based on alignment metrics
FROGS Abundance normalisation Normalise ASV abundance.

Optional basic tools

FROGS BIOM to std BIOM Converts a FROGS BIOM in fully compatible BIOM
FROGS TSV_to_BIOM Converts a TSV file in a BIOM file 1
FROGS BIOM to TSV Converts a BIOM file in TSV file


Utilities tools

FROGSFUNC_1_placeseqs_and_copynumbers Places ASVs into a reference phylogenetic tree.
FROGSFUNC_2_functions Calculates functions abundances in each sample.
FROGSFUNC_3_pathways Calculates pathway abundances in each sample.

Functional inference tools




28 tools
in total



Pre-process tool

For short reads from illumina



Are reads already merged ?

No

Yes = The archive contains 1 file by sample : R1 and R2 pairs are already merged in one sequence.

Reads 1 size

300

The maximum read1 size.

Reads 2 size

300

The maximum read2 size.

Mismatch rate


0.1

The maximum rate of mismatches in the overlap region (--mismatch-rate)

Merge software

Vsearch

Select the software to merge paired-end reads (--merge-software)

You need to keep unmerged reads (ITS, ...) 

Would you like to keep unmerged reads?

No, unmerged reads will be excluded.


Yes, unmerged reads will be artificially combined.

No = Unmerged reads will be excluded; Yes = unmerged reads will be artificially combined with 100 N. (default No) (--keep-unmerged)

Are reads already merged ?

Yes

Yes = The archive contains 1 file by sample : R1 and R2 pairs are already merged in one sequence.

**Sequencer**

Illumina

Select the sequencing technology used to produce the sequences.

Input type

TAR Archive

Samples files can be provided in a single TAR archive or sample by sample (with one or two files each).

TAR archive file 1: ITS_fast.tar.gz

The TAR file containing the sequences file(s) for each sample.

Are reads already merged ?

No

Yes = The archive contains 1 file by sample : R1 and R2 pairs are already merged in one sequence.

Reads 1 size

250

The maximum read1 size.

Reads 2 size

250

The maximum read2 size.

Mismatch rate

0.1

The maximum rate of mismatches in the overlap region (--mismatch-rate)

Merge software

Vsearch

Select the software to merge paired-end reads (--merge-software)


Would you like to keep unmerged reads?

- No, unmerged reads will be excluded.
- Yes, unmerged reads will be artificially combined.

No = Unmerged reads will be excluded; Yes = unmerged reads will be artificially combined with 100 N. (default No) (--keep-unmerged)



To keep FROGS combined sequences, choose YES

**Minimum amplicon size**

180

The minimum size of the amplicons (with primers) (--min-amplicon-size)

Maximum amplicon size

490

The maximum size of the amplicons (with primers) (--max-amplicon-size)

Do the sequences have PCR primers? Yes No**5' primer**

CTTGGTCATTTAGAGGAAGTAA

The 5' primer sequence (wildcards are accepted). This primer must be written in 5' to 3' orientation (see details in 'Primers parameters' help section) (--five-prim-primer)

3' primer

GCATCGATGAAGAACGCAGC

The 3' primer sequence (wildcards are accepted). This primer must be written in 5' to 3' orientation (see details in 'Primers parameters' help section) (--three-prim-primer)

Primer 5': CTTGGTCATTTAGAGGAAGTAA

Primer 3': GCATCGATGAAGAACGCAGC

Exercise


Go to « [ITS](#) » history


Launch the pre-process tool on this data set

→ objective: understand preprocess report and « FROGS combined sequences »

Explore Preprocess report.html

Preprocess summary





2 tables:

Details on merged sequences

Show 10 entries

CSV

Search:

Samples	before process	% kept	paired-end assembled	with 5' primer	with 3' primer	with expected length	without N
Ph203	10,000	79.42	7,954	7,948	7,942	7,942	7,942
Ph212	10,000	78.28	7,837	7,832	7,828	7,828	7,828
Ph217	10,000	80.48	8,061	8,052	8,048	8,048	8,048
Ph222	10,000	78.34	7,839	7,835	7,834	7,834	7,834

Own tag for combined sequences

```

>M01328:521:000000000-KRPT:1:1103:15714:11240;size=6 1:N:0:238
AAGTCGTAACAAGGTAACCGTAGGTGAACCTGCGGTTGGATCATTAAAAATTTATGAGTTCCGTTGAC
>M01328:521:000000000-KRPT:1:2102:7650:15129;size=1 1:N:0:239
AAGTCGTAACAAGGTAACCGTAGGTGAACCTGCGGTTGGATCATTAAAAATTTATGAGTTCCGTTGAC
>M01328:521:000000000-KRPT:1:1112:8680:15899;size=1 1:N:0:202
AAGTCGTAACAAGGTTATCGTTGCACTAGCTAAGCCCTATTGCAAGCCTTTCCAGCGACTGAAAAAATAC
>M01328:521:000000000-KRPT:1:1111:21036:16514_FROGS_combined;size=1
AAGTCGTAACAAGGTTCCGTTAGGTGAACCTGCGGTAAGGATCATTACAAGTTCTGTAGGTCTGTCGCA
>M01328:521:000000000-KRPT:1:1106:19343:17084_FROGS_combined;size=1
AAGTCGTAACAAGGTTCCGTTAGGTGAACCTGCGGTAAGGATCATTACAAGTTCTGTAGGTCTGTCGCA

```

Details on artificial combined sequences

Show 10 entries

CSV

Search:

Samples	before process	% kept	paired-end assembled	with 5' primer	with 3' primer	with expected length	without N
Ph203	10,000	19.68	2,046	2,038	1,968	1,968	1,968
Ph212	10,000	20.65	2,163	2,154	2,065	2,065	2,065
Ph217	10,000	18.63	1,939	1,928	1,863	1,863	1,863
Ph222	10,000	20.79	2,161	2,155	2,079	2,079	2,079

Filter only on minimum length for « combined ».

Minimum length =
 $R1 + 100N + R2 - \text{primers sizes}$

If the primers are very internal to the read, after trimming them, the combined sequence could be smaller than a read. FROGS rejects these cases.



FROGS_0 Demultiplex reads Attribute reads to samples in function of inner barcode
FROGS_1 Pre-process merging, denoising and dereplication
FROGS_2 Clustering swarm Single-linkage clustering on sequences
FROGS_Cluster_Stat Process some metrics on clusters
FROGS_3 Remove chimera Remove PCR chimera in each sample
FROGS_4 Cluster filters Filters clusters on several criteria.
FROGS ITSx Extract the highly variable ITS1 and ITS2 subregions from ITS sequences
FROGS_5 Taxonomic affiliation Taxonomic affiliation of each ASV's seed by RDPtools and BLAST
FROGS_6 Affiliation_Stat Process some metrics on taxonomies

Basic tools

FROGSSTAT Phyloseq Import Data from 3 files: biomfile, samplefile, treefile
FROGSSTAT Phyloseq Composition Visualisation with bar plot and composition plot
FROGSSTAT Phyloseq Alpha Diversity with richness plot
FROGSSTAT Phyloseq Beta Diversity distance matrix
FROGSSTAT Phyloseq Sample Clustering of samples using different linkage methods
FROGSSTAT Phyloseq Structure Visualisation with heatmap plot and ordination plot
FROGSSTAT Phyloseq Multivariate Analysis Of Variance perform Multivariate Analysis of Variance (MANOVA)
FROGSSTAT DESeq2 Preprocess import a Phyloseq object and prepare it for DESeq2 differential abundance analysis a
FROGSSTAT DESeq2 Visualisation extract and visualise differentially abundant ASVs or functions

Statistics tools

FROGS Tree Reconstruction of phylogenetic tree
FROGS Affiliation Filters Filters ASVs on several affiliation criteria
FROGS Affiliation postprocess Aggregates ASVs based on alignment metrics
FROGS Abundance normalisation Normalise ASV abundance.

Optional basic tools


FROGS BIOM to std BIOM Converts a FROGS BIOM in fully compatible BIOM
FROGS TSV_to_BIOM Converts a TSV file in a BIOM file 1
FROGS BIOM to TSV Converts a BIOM file in TSV file

Utilities tools


FROGSFUNC_1_placeseqs_and_copynumbers Places ASVs into a reference phylogenetic tree.
FROGSFUNC_2_functions Calculates functions abundances in each sample.
FROGSFUNC_3_pathways Calculates pathway abundances in each sample.

Functional inference tools

28 tools
in total




ITSx tools




What is the purpose of the ITSx tool?

- ITSx is a tool to **filter** sequences.
- ITSx **identifies** and **trimms** ITS regions in sequences.
- It **excludes** the highly conserved neighboring sequences **SSU**, **5S** and **LSU** rRNA.
- If the ITS1 or ITS2 region is not detected, the sequence is discarded.
- You can choose to check only if the sequence is detected as an ITS.
In this case, the sequence is not trimmed, only sequences not detected as ITS are rejected (*e.g.* contaminants).



Bengtsson-Palme, J., et al. (2013), Improved software detection and extraction of ITS1 and ITS2 from ribosomal ITS sequences of fungi and other eukaryotes for analysis of environmental sequencing data. *Methods Ecol Evol*, 4: 914-919.
<https://doi.org/10.1111/2041-210X.12073>

What is the purpose of the ITSx tool?




1st case: choose to trim
 ITS1 is well detected
 SSU part and 5.8S part are trimmed
 Result: —————

2nd case: choose to check only
 ITS1 is well detected
 SSU part and 5.8S part are not trimmed
 Result: —————

Check only if sequence is detected as ITS? Yes or not?


- If not, only ITS1 or ITS2 part will be conserved
- This is interesting to keep only the ITS parts without the flanking sequences in case of :
 - comparison of sequenced amplicons with different primers targeting the same region to be amplified.
 - using a database with only ITS part





When should we use ITSx ?





Sequence file

16: FROGS_4 Cluster filters: clusterFilters_sequences.fasta

The sequence file to filter (format: FASTA).

Abundance file

15: FROGS_4 Cluster filters: clusterFilters_abundance.biom

The abundance file to filter (format: BIOM)

Trim conserved sequence (SSU, 5.8S, LSU) ?

No, keep conserved regions
 Yes, trim conserved regions

If Yes, only part of the sequences with ITS signature will be kept, SSU, LSU or 5.8S regions will be trimmed (default : No) (--check-its-only)

Choose pertinent organisms to scan:

Select/Unselect all

- Fungi
- Alveolata
- Bryophyta
- Bacillariophyta
- Amoebozoa
- Euglenozoa
- Chlorophyta
- Rhodophyta
- Phaeophyceae
- Marchantiophyta
- Metazoa
- Oomycota
- Haptophyceae
- Raphidophyceae
- Rhizaria
- Synurophyceae
- Tracheophyta
- Eustigmatophyceae

Save a lot of time by checking pertinent organism group model to scan (--organism-groups)

Email notification

No

Send an email notification when the job completes.

By default, the ITSs are kept in their entirety.


By default, sequences are considered as FUNGI sequences. Change it, if it is not the case.

Careful !



- The ITSx step is time consuming and has to be done on minimum of clusters.
 1. Preprocess step,
 2. Clustering step,
 3. Chimera removing step,
 4. Filter on ASVs abundances and replicates step,
 5. ITSx

Filters (ITSx) summary




Filters (ITSx) by samples

 CSV
Show entriesSearch:

ASVs removed by sample

Sample name	Initial	Kept	Initial abundance	Kept abundance
Ph203	105	105	7,065	7,065
Ph212	65	65	7,474	7,474
Ph217	89	89	5,990	5,990



FROGS_0 Demultiplex reads Attribute reads to samples in function of inner barcode
FROGS_1 Pre-process merging, denoising and dereplication
FROGS_2 Clustering swarm Single-linkage clustering on sequences
FROGS_Cluster_Stat Process some metrics on clusters
FROGS_3 Remove chimera Remove PCR chimera in each sample
FROGS_4 Cluster filters Filters clusters on several criteria.
FROGS ITSx Extract the highly variable ITS1 and ITS2 subregions from ITS sequences
FROGS_5 Taxonomic affiliation Taxonomic affiliation of each ASV's seed by RDPtools and BLAST
FROGS_6 Affiliation_Stat Process some metrics on taxonomies

Basic tools

FROGSSTAT Phyloseq Import Data from 3 files: biomfile, samplefile, treefile
FROGSSTAT Phyloseq Composition Visualisation with bar plot and composition plot
FROGSSTAT Phyloseq Alpha Diversity with richness plot
FROGSSTAT Phyloseq Beta Diversity distance matrix
FROGSSTAT Phyloseq Sample Clustering of samples using different linkage methods
FROGSSTAT Phyloseq Structure Visualisation with heatmap plot and ordination plot
FROGSSTAT Phyloseq Multivariate Analysis Of Variance perform Multivariate Analysis of Variance (MANOVA)
FROGSSTAT DESeq2 Preprocess import a Phyloseq object and prepare it for DESeq2 differential abundance analysis
FROGSSTAT DESeq2 Visualisation extract and visualise differentially abundant ASVs or functions

Statistics tools

FROGS Tree Reconstruction of phylogenetic tree
FROGS Affiliation Filters Filters ASVs on several affiliation criteria
FROGS Affiliation postprocess Aggregates ASVs based on alignment metrics
FROGS Abundance normalisation Normalise ASV abundance.

Optional basic tools

Not specific for ITS
but often useful


FROGS BIOM to TSV Converts a BIOM file in TSV file
FROGS TSV to BIOM Converts a TSV file in a BIOM file

Utilities tools

FROGSFUNC_1_placeseqs_and_copynumbers Places ASVs into a reference phylogenetic tree.
FROGSFUNC_2_functions Calculates functions abundances in each sample.
FROGSFUNC_3_pathways Calculates pathway abundances in each sample.

Functional inference tools

28 tools
in total



Affiliation Post-process




What is the purpose of the *Affiliation post-process* tool ?

This tool allows **grouping ASVs together** in accordance with the %id and %cov chosen by the user and according to the following criteria:

1. They must have the same affiliation

Or

2. If they have "multi-affiliation" tag in FROGS taxonomy, they must have in common in their list of possible affiliations at least one identical affiliation.




What is the purpose of the *Affiliation post-process* tool ?

In consequence:

The different affiliations involved in multi-affiliation are merged.

The abundances are added together.

It is the most abundant ASV seed that is kept.



Sequence file

21: FROGS ITSx: ITS_sequence.fasta

The sequence file to filter (format: FASTA).

Abundance file

25: FROGS_5 Taxonomic affiliation: affiliation_abundance.biom

The abundance file to filter (format: BIOM)

Is this an amplicon hyper variable in length?

- No
- Yes

Yes, we have combined sequences

Multi-affiliation tag may be resolved by selecting the shortest amplicon reference. For this, you need the reference fasta file of your target amplicon.

Using reference database

UNITE 8.2 ITS1

same database used for taxonomic affiliation

Select reference from the list (--reference)

Minimum identity for aggregation

99

ASVs will be aggregated if they share the same taxonomy with at least X% identity (--identity)

Minimum coverage for aggregation

99

ASVs will be aggregated if they share the same taxonomy with at least X% alignment coverage (--coverage)

Here, we wanted to aggregate ASVs only if they are very closed

Email notification

No

Send an email notification when the job completes.

✓ Execute

FROGS Affiliation postprocess: OTU_aggregation_composition.txt

FROGS Affiliation postprocess: sequences.fasta

FROGS Affiliation postprocess: affiliation_abundance.biom

Cluster_1

Cluster_2

Cluster_8

Cluster_3

Cluster_5

Cluster_4

Cluster_6

Cluster_7

Cluster_9

Cluster_13

Cluster_10

Cluster_11

Cluster_16

Cluster_17

Cluster_14

Cluster_12

Cluster_15

Cluster_22

Cluster_18

Cluster_23

Cluster_25

Cluster_19

Cluster_21

Cluster_26

Cluster_29

Cluster_34

Cluster_35

Cluster_28

Cluster_31

Cluster_32


Cluster_42

Cluster_33

Cluster_75_FROGS_combined Cluster_121_FROGS_combined Cluster_137_FROGS_combined Cluster_144_FROGS_combi




Workflow creation




Workflows are useful for routine analyses

A workflow links FROGS steps together and when it is launched, all the steps run automatically.



Practice

CREATE YOUR OWN WORKFLOW !



Exercise



New Galaxy server, needed tools/databanks are added on demand

Tools

search tools

Upload Data

BASIC TOOLS

- Monitoring
- Get Data
- Send Data
- Collection Operations
- Lift-Over
- Text Manipulation
- Convert Formats
- Filter and Sort

Search Workflows

+ Create Import

Name	Tags	Updated	Sharing	Bookmarked
16S		a few seconds ago		<input type="checkbox"/>
ITS		2 minutes ago		<input type="checkbox"/>

History

Rechercher des données

ITS

21 shown

252.24 MB

- 21: FROGS Affiliation O TU: report.html
- 20: FROGS Affiliation O TU: affiliation_abundance.biom
- 19: FROGS ITSx: report.html
- 18: FROGS ITSx: itsx_abundance.biom

Exercise

Create Workflow

Name

3

ITS_formation


Annotation

A description of the workflow; annotation is shown alongside shared or published workflows.

✕ Cancel

✓ Create

4



Exercise

Search Workflows

+ Create Import


Name	Tags	Updated	Sharing	Bookmarked	
▼ ITS_formation		a few seconds ago		<input type="checkbox"/>	
▼ 16S		3 minutes ago		<input type="checkbox"/>	
▼ ITS		5 minutes ago		<input type="checkbox"/>	




Name Tags



▼ ITS_formation

- Edit
- Copy
- Download
- Rename
- Share
- View
- Delete



Solution of exercise:





FROGS_2 Clustering swarm Single-linkage clustering on sequences (Galaxy Version 4.1.0+galaxy1)

Label

Add a step label.

Step Annotation

Add an annotation or notes to this step. Annotations are available when a workflow is viewed.

Sequences file
Data input 'sequence_file' (fasta)
The dereplicated sequences file (format: FASTA)

Count file
Data input 'count_file' (tabular or tsv)
It contains the count by sample for each sequence (format: TSV)

FROGS guidelines version
New guidelines from version 3.2

The denoising step before a d3 clustering is no longer recommended since FROGS 3.2, but you can still choose it.

↔ Aggregation distance clustering
1

Maximum number of differences between sequences in each aggregation Swarm step. (recommended d=1) (--distance)


↔ Refine clustering

Yes, refine clustering with --fastidious swarm option
 No, perform clustering without refinement


Clustering will be performed with the Swarm --fastidious option. It is recommended and only usable in association with a distance of 1 (default and recommended: Yes) (--fastidious)

For each tool, think to:

1. Set parameters



Configure Output: 'FROGS Clusters stat: report.html'



Configure Output: 'FROGS Clusters stat: report.html'

Label

Don't use label

This will provide a short name to describe the output - this must be unique across workflows.

Rename dataset

This action will rename the output dataset. Click here for more information. Valid input variables are:

- **biom** (Abundance file)

Change datatype

Leave unchanged

This action will change the datatype of the output to the indicated datatype.

Add Tags

This action will set tags for the dataset.

Remove Tags


This action will remove tags for the dataset.

Assign columns

For each tool, think to:


1. Set parameters
2. Rename output files





For each tool, think to:

1. Set parameters
2. Rename output files
3. Hide intermediate files to simplify your history



Exercise

When your workflow is built

1. Run your own workflow with ITS data with :

[ITS fast.tar.gz](#)

[ITS fast metadata.tsv](#)

[ITS fast replicates.tsv](#)

2. Run FROGSSTAT tools